



Refresher

Water-based maintenance product for indoor use

For professional and private use.

A water-based maintenance product for indoor wooden floors sealed with one of Junckers water or oil based lacquers. Suited for domestic and commercial areas. Revives a dull looking surface, hides minor scratches and protects the floor.

Gloss:

Silk Matt

Package Size:

5 Litres,

Technical Information

GENERAL DESCRIPTION

A water based maintenance product for indoor wooden floors sealed with one of Junckers water or oil based lacquers.

Revives a dull looking surface, hides minor scratches and protects the floor.

Suited for domestic and commercial areas.

Junckers Refresher is specially formulated to allow it to be over coated with Junckers lacquers as and when required this is – only a light sanding before adding a new coat of Junckers lacquer is necessary.

PRODUCT DESCRIPTION

Product: Water-based acrylic/polyurethane.

Appearance: Creamy/milky in the container. Colourless film when dry.

TECHNICAL DATA

Coverage: 20-25 m² per litre.

Before application: Shake well before use.

Application tools: Flat floor mop

Surface temperature: Minimum 15° C and maximum 25° C.

Dilution: Delivered ready for use. Dilution is not recommended.

Drying time at 20° C and 50 % RH - NY:

Approx. 1-2 hours.

Ready for light traffic after 3 hours.

Retreatment after 3 hours.

Apply only 2 coats per day.

Fully cured after 72 hours.

Cleaning of tools: Soap and water immediately after use

Storage: Lasts 1 year if unopened and stored at 20° C. Not to be exposed to temperatures below 5° C.

SYSTEM RECOMMENDATIONS

All areas: 1-2 coats of Junckers Refresher.

The frequency of treatment depends on foot traffic levels. Floors with higher levels of traffic will require treatment more often.

DIRECTION FOR USE

Maintenance of sound and stable lacquered floors:

The lacquered surface must be absolutely clean, dry and free from dust, grease, polish and detergent residue. Dirt and irregularities can be removed by using Junckers Sylva Cleaner and/or JunckersNeutralizer.

It is important to ensure that the existing lacquer is intact and is one of Junckers lacquer products before applying Junckers Refresher.

Always conduct a trial application in an inconspicuous area. After drying check the appearance of the floor and adhesion by scraping with the edge of a coin.

Apply an even thin layer and allow to dry. It is recommended to work in smaller sections, avoiding overlaps and keeping a wet edge during application.

Surfaces worn through:

If the existing lacquer surface has worn through, the floor must first be sanded followed by priming and sealing with one of Junckers lacquer systems.

PRECAUTIONARY MEASURES

Before using the product, read the label on the container carefully and observe the recommended precautionary measures. See Material Safety Data Sheet for detailed information about precautionary measures.

FURTHER INFORMATION

Products:

F 10.2 – Junckers SylvaCleaner

F 10.3 - Junckers SylvaNeutralizer
