

SB FILLER

PRODUCT INFORMATION



GENERAL DESCRIPTION

- A fast-drying solvent-based gap filler designed to fill joints and gaps in wooden floor.
- Particularly suitable for industrial parquet and patterned floors such as herringbone flooring.
- Mixed with sanding dust, the filler can be used to fill gaps up to 2 mm wide.
- SB Filler can be used in combination with Junckers floor oils and lacquers.

For professional use.

PRODUCT DESCRIPTION

Product: Solvent-based filler to be mixed with sanding dust.

Package sizes: 5 litres.

Appearance: Colourless.

TECHNICAL DATA

Coverage: Approx. 10 m² per litre.

Before application: Shake/stir well before use.

Application tools: Broad full-edged spatula of stainless steel.

Substrate temperature: Minimum 15 °C.

Dilution: Not recommended.

Drying time at 20 °C and 50 % RH:

Approx. 30-45 minutes depending on the depth of the joints.

Cleaning of tools: Methylated spirits.

Storage: Lasts for 2 years if unopened and stored at 20 °C.

DIRECTIONS FOR USE

Untreated/sanded floors:

- Ensure that the surface is clean, dry and free from dust, wax, oil, lacquer, grease, polish and soap residues.
- The final sanding before application should be carried out with 120-150 grit sandpaper.
- Mix sanding dust into the filler until a thick but spreadable paste is obtained.
- Spread the paste using a stainless steel spatula.
- When dry, sand with 150-180 grit sandpaper.
- Vacuum thoroughly and proceed with oil or lacquer application.

PRECAUTIONARY MEASURES

Before using the product, read the label on the container carefully and observe the recommended precautionary measures. See Safety Data Sheet for detailed information.